Capping Compound Warming Pots 220vAC

Code: 34-6125/01
Product Group: Capping Compound Warming Pots

4 Qt. (3.7 liter) capacity.

Further Information

220vAC, 50/60
Hz, 1ø. 1,250 Watts.220vAC, 50/60
Hz, 1ø. 1,250 Watts.220vAC, 50/60
Hz, 1ø. 1,250 Watts.220vAC, 50/60
Hz, 1ø. 1,250 Watts.220vAC, 50/60
Hz, 1ø. 1,250 Watts.220vAC, 50/60
Hz, 1ø. 1,250 Watts.

Specification

Capacity	4 qt. (3.7 liters).
Temperature Range	150Â°F to 45 0Â°F (65Â°C to 25 0Â°C).
Control	Adjustable, automatic thermostat with pilot light.
Construction	Round aluminum pot with steel jacket; with cover.
Inside Dimensions	8â diam. x 5-1/2â d. (203 x 14 0 mm).
Outside Dimensions	9â diam. x 10â h. (22 9 x 254 mm).
Weights	Shpg. 13 lbs. (5.9 kg).

Accessories

Capping Ladle

Code: 81-0701

Flake Capping Compound to ASTM C617 22Kg

Code: 34-6100

Alternatives

4" Compression Pads 60 Durometer

Code: 34-6132/10

4" Compression Pads 70 Durometer

Code: 34-6132/12

4" Retaining Caps

Code: 34-6132

6" Compression Pads 60 Durometer

Code: 34-6134/10

6" Compression Pads 70 Durometer

Code: 34-6134/12